

RelyEZ VenturePro Series

250kWh
All-in-one



VenturePro 250 —

250 kWh
(BMS),

PCS.

VenturePro 250
LFP-

52 kWh.

RelyEZ

5
314 h. 52



90%



VenturePro
LFP-

		IEC		UL
	PCS	IP 65		
		IP 67		
	PCS	IEC/EN 62477-1, EN IEC 61000-6-2, EN IEC 61000-6-4, EN50549-1	UL1741, CSA C22.2 No. 107.1-16, CLASS - C531109, CLASS - C531189, CSA C22.2 No. 107.1-16, IEEE 1547.1-2020, IEEE 1547-2018, IEEE 1547a- 2020	
		IEC62619	UL1973, UL9540A	
		IEC60730-1, UN38.3	UL9540A, UL1973, UL60730-1, UN38.3	
		EN 62477-1 EN IEC 61000-6-2/4 UN38.3, UN3480	UL9540, UL9540A, FCC part 15B, UN38.3, UN3480	
(DC)		1P260S		
		250 kWh		
		832 Vdc		
		728 ~ 936 Vdc		
		≥8000 cycles		
(AC)		125 kW		
		400 Vac	480 Vac	
		180 A	150 A	
		-15% ~ +10%	-10% ~ +5%	
		50/60 Hz	60 Hz	
		±5 Hz	±3 Hz	
		< 20 ms		
		< 3% (rated working condition)		
		< 0.5%		
		< 3% (linear load)		
		90% (without aux. consumption)		
		-30°C to 55°C (-22°F to 122°F)		
		0 - 95%		
		-30°C to 55°C (-22°F to 122°F)		
	()	≤2000 m		
		≤75 dB (1 m)		
	(W x D x H)	1350 x 1400 x 2250(2340)mm(53.15 x 55.12 x 88.58(92.13)in)		
		≤ 3500 kg		
	IP	IP 54		
	ÿÿ	CAN / Modbus-TCP/RTU		
		Aerosol		
		Liquid-Cooling		
		5 years (included)		
		5 / 10 years		