

RelyEZ VenturePro Fusion



VenturePro Fusion —
VenturePro.

1 8

0,261 MWh 3,344 MWh.

VenturePro Fusion

BMS,



More quick-plug designs reduce the need for on-site assembly.



93%

(DC)



		YXYK-552314-E	YXYK-652314-E	YXYK-752314-E	YXYK-852314-E
		1P260S	1P312S	1P364S	1P416S
		261.248 kWh	313.498 kWh	365.747 kWh	417.997 kWh
		DC 832 V	DC 998.4 V	DC 1164.8 V	DC 1331.2 V
		DC 728~936 V	DC 873.6~1123.2 V	DC 1019.2~1310.4 V	DC 1164.8~1497.6 V
		MAX 93%			
		157 A			
		179.4 A			
		130.642 kW	156.749 kW	182.874 kW	208.998 kW
		AC 220 V, 50 Hz / 60 Hz			
		MAX 3.7 kW			
		-30°C to 55°C (-22°F to 131°F)			
		-30°C to 55°C (-22°F to 131°F)			
	(L x W x H)	1350 x 1310 x 2434 mm (53.15 x 51.57 x 95.83 in)			
		About 3.0 T (6613.86 lb)	About 3.3 T (7273.446 lb)	About 3.6 T (7936.632 lb)	About 3.9 T (8598.018 lb)
	IP	IP 54			
		Aerosol			
		Liquid-Cooling			
) (≤2000 m / <3000 m (available, derate) ≤6562 ft / <9843 ft (available, derate)			
	/	UL9540, UL9540A, UL1973, IEC 62619, IEC 63056, IEC 62477-1, UN38.3, UN3480			
		UL9540, FCC part 15B, IEC 62477-1, EN/IEC 61000-6-2/4			

		DC 728~1497.6 V
		1435.43 A
		1671.984 kW
		AC 480 V(UL)/AC 400 V(IEC), 50 Hz / 60 Hz
		MAX 30 kW
		-30°C to 55°C (-22°F to 131°F)
		-30°C to 55°C (-22°F to 131°F)
(L x W x H)		1350 x 900 x 2414 mm (53.15 x 35.43 x 95.08 in)
		About 0.9 T (1984.158 lb)
IP		IP 54
) (≤2000 m / <3000 m (available, derate) ≤6562 ft / <9843 ft (available, derate)
		IEC 62619, IEC 63056, IEC/EN 62477-1, EN 61000-6-4, UN 38.3, UN 3480

